

132cells Monocrystalline Bifacial Dual Glass Module

APEX-132HBD-N695-N720M12

N-TOPCon Technology

23.20%

Maximum Module Efficiency

720W

Maximum Power Output

Power Tolerance:0-3W

2384×1303×35mm

Module Dimensions

IEC 61215 / IEC 61730

Fire safty class:Class A according to UL790


ISO 9001 :Quality Management System

ISO 14001 :Environment Management



Industry Leading Linear Power Warranty

25-year Warranty for Materials and Processing, 30-year Warranty for Extra Linear Power Output



25 Process Warranty

30 Power Warranty

High Efficiency Half-cells Solar Panel APEX-132HBD-N695-N720M12

ELECTRICAL PARAMETERS AT STC

Rated Maximum Power(Pmax) [W]	695	700	705	710	715	720
Maximum Power Voltage(Vmp) [V]	40.30	40.50	40.70	40.90	41.10	41.30
Maximum Power Current(Imp) [A]	17.25	17.29	17.33	17.36	17.40	17.44
Open Circuit Voltage(Voc) [V]	48.30	48.60	48.80	49.00	49.20	49.40
Short Circuit Current(Isc) [A]	18.28	18.32	18.36	18.40	18.44	18.49
Module Efficiency [%]	22.40	22.50	22.70	22.90	23.00	23.20

STC: Irradiance 1000 W/m2 module temperature 25°C AM=1.5

ELECTRICAL PARAMETERS AT NMOT

Rated Maximum Power(Pmax)[W]	531	534	540	543	547	551
Maximum Power Voltage(Vmp) [V]	37.90	38.00	38.30	38.50	38.70	38.80
Maximum Power Current(Imp) [A]	14.00	14.04	14.08	14.12	14.14	14.19
Open Circuit Voltage(Voc) [V]	45.90	46.10	46.30	46.50	46.70	46.90
Short Circuit Current(Isc) [A]	14.72	14.76	14.80	14.83	14.86	14.90

NMOT: Irradiance 800 W/m2 ambient temperature 20°C wind speed: 1m/s

BIFACIAL OUTPUT-REAR SIDE POWER GAIN

5%	Maximum Power (Pmax) [W]	730	735	740	746	751	756
	Module Efficiency STC[%]	23.49	23.66	23.83	24.00	24.17	24.34
10%	Maximum Power (Pmax) [W]	765	770	776	781	787	792
	Module Efficiency STC[%]	24.61	24.79	24.96	25.14	25.32	25.50
20%	Maximum Power (Pmax) [W]	834	840	846	852	858	864
	Module Efficiency STC[%]	26.85	27.04	27.23	27.43	27.62	27.81

MECHANICAL SPECIFICATION

Cell Type	N-Type Monocrystalline
Cell Dimensions	210×210mm
Cell Arrangement	132(6×22)
Weight	38.3kg(±3%)
Module Dimensions	2384×1303×35mm
Cable	4.0 mm ² positive/negative:300mm(11.8inches),length Can be customized
Front Glass	2.0 mm (0.08 inches), High Transmission, ARCoated Heat Strengthened Glass
Back Glass	2.0 mm (0.08 inches), Heat Strengthened Glass (White Grid Glass)
Frame	Anodized aluminium alloy
Junction Box	Protection class IP68
Connector	Mc4 Compatible
Mechanical Load	Front side 5400Pa/Rear side 2400Pa



OPERATING CONDITIONS

Maximum System Voltage (V)	1000/1500VDC (IEC)
Pmax Temperature Coefficient	-0.34%/°C
Voc Temperature Coefficient	-0.28%/°C
ISC Temperature Coefficient	+0.05%/°C
Nominal Operating Cell Temperature	45±2°C
Operating Temperature	- 40°C -+85°C
Maximum Series Fuse	35A


PACKING CONFIGURATION

Quantity/Pallet	31pcs/pallet
Quantity/Container	558pcs/40HQ

Module Dimension(mm)



Current-Voltage Curve (720W)



Power-Voltage Curve (720W)

